

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 July 2001 (19.07.2001)

PCT

(10) International Publication Number
WO 01/52483 A1

(51) International Patent Classification⁷: **H04L 12/56**

(21) International Application Number: **PCT/AU01/00015**

(22) International Filing Date: 11 January 2001 (11.01.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 5041 ✓ 11 January 2000 (11.01.2000) AU

(71) Applicant (for all designated States except US):
STREAMING MEDIA AUSTRALIA PTY LTD.
[AU/AU]; Suite 301, Level 3, No 3 Smail Street, Broadway, NSW 2007 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LEAR, Ben Adair**

[AU/AU]; Benroe Spring Flat, Mudgee, NSW 2850 (AU).
HAYES, Joseph, Francis [AU/AU]; 15 Coolabah Crescent, Forestville, NSW 2087 (AU).


(74) Common Representative: **STREAMING MEDIA AUSTRALIA PTY LTD.**; ARMAN, Mark, Suite 301, Level 3, No. 3 Smail Street, Broadway, NSW 2007 (AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: **SYSTEM AND METHOD FOR DISTRIBUTION OF DATA PACKETS UTILIZING AN INTELLIGENT DISTRIBUTION NETWORK**



(57) Abstract: A system and method for efficient distribution of streamed media content to large and diversely located client locations is provided whereby an intelligent distribution network (IDN) center manages the delivery of the streamed media to a plurality of clients. The IDN center determines the most efficient delivery route to each client by utilizing trace routes between the IDN center, IDN nodes, various transmission devices and the client. Once a "best performing" IDN node and network link is determined, the IDN center directs the client to the "best" node and instructs delivery of a content stream along the "best" link. Upon receiving the streamed media, the "best" node replicates the stream and delivers the media to the client. Additional clients may "piggyback" off the initial content stream by obtaining a replication of the media from their "best" nodes which are, or connected to nodes, already transmitting/receiving the initial content stream.

- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

— *with international search report*

**SYSTEM AND METHOD FOR DISTRIBUTION OF DATA PACKETS
UTILIZING AN INTELLIGENT DISTRIBUTION NETWORK**

CROSS-REFERENCE TO RELATED APPLICATION

5 This application claims the priority and benefit of Australian
Provisional Patent Application Serial No. PQ5041 entitled "A Method for
Distribution of Streamed Data Packets on a Switched Network Utilizing an
Intelligent Distribution Network," filed on January 11, 2000, the subject
matter of which is hereby incorporated by reference.

10

BACKGROUND

1. **Technical Field**

 The present system and method relate generally to network data
transmission, and more particularly to efficient distribution of data utilizing
15 an intelligent distribution network.

2. **Description of the Background Art**

 The Internet is a network of virtually connected computers and
network-enabled devices currently using Transfer Control Protocol (TCP)
20 and Internet Protocol (IP). TCP/IP is a combination of these two means to
deliver data from a host to a client, which involves the breaking down of
large data blocks into a plurality of small data packets for transmission by
asynchronous transmission electronic devices. Each packet contains packet
order information such that when it arrives at a client, the packets can be
25 contiguously reordered even if packets do not arrive in the correct packet
order due to intrinsic network behavior. Furthermore, TCP can decide
based on intrinsic packet timing criteria whether a packet has been lost or
unacceptably delayed, which may result in a subsequent request by the
client for a retransmission of the lost or delayed packets. Thus, the greater

the number of lost or unacceptably delayed packets, the greater overall decrease to network throughput and increased latency.

When a data packet is transmitted from a host to a client, it passes through various asynchronous transmission devices such as routers, switches, hubs and bridges. Typically, the data packet may incur a latency of approximately 40ms per transmission device. Because there are numerous paths of varying number of transmission devices that a data packet may travel, a contiguous set of data packets sent from a host may incur considerable timing disruptions making it impossible for the packets to arrive at the client in a contiguous order. Additionally the total delay time for data packet transmission may exceed acceptable ergonomic requirements.

Theoretically, these transmission devices are limited by maximum capacity or bandwidth. For example, a client can presently link to an Internet Service Provider (ISP) through a Public Standard Telephone Network (PSTN) Connection with a modem at a bandwidth capacity typically of fourteen thousand, four hundred bits per second to sixty four thousand bits per second. Alternatively, Broadband Internet Service Providers (BISP) offer larger bandwidth capacity, but essentially function in a similar role of connecting the client to a router at the ISP.

All data to and from clients are combined at the ISP. This combined data can be managed more efficiently as the asynchronous transmission devices are located within the ISP Local Area Network (LAN) that has typical bandwidths of many gigabits per second. Therefore, data that is available within the LAN can be sent to clients of that ISP with maximum network throughput and minimal loss of packets or unacceptable delay. However, when requested information is found outside of the ISP LAN, the Wide Area Network (WAN) is used to connect the ISP or BISP to the host electronic location. Typically bandwidth throughput of the devices in the

WAN is less than those of the ISP LAN. Additionally, the cost of use of the WAN is often far higher than that of the LAN.

The Internet was initially perceived and designed to carry text-based e-mail and Hyper Text Transfer Protocol (HTTP) encoded documents.

- 5 Performance of the Internet using HTTP and text based e-mail is not critically time dependent, thus intrinsic latency of the Internet infrastructure is ergonomically acceptable and utilization of bandwidth is minimal. However, data size and demand has increased through the introduction of concepts such as multimedia content data, which intrinsically contains
- 10 significantly larger data size. This results in performance problems for real time applications where network timing and sustained data rates are critical. Such applications include streaming media and packet switched telephone networks.

- FIG. 1 illustrates the transmission of a data stream from a content
- 15 server 102 to ISP1 104, ISP2 106 and ISP3 108 and eventually to various end users, via ISP Points Of Presence (POPs) 109, 110, 111, 112, 113, 114, 115, 116, 117. As shown, conventional methods of distribution require a separate transmission for each request from each end user through their respective ISPs 104, 106 and 108. Because the ISP LANs do not contain the requested
- 20 data, the data must be distributed from the content server 102 through the WAN. However, this method of data transmission presents several problems to both the end users and the ISPs. First, the distribution of streamed data is seriously restricted due to general lack of bandwidth capacity caused by redundant and duplicated transmission to multiple
- 25 viewers. As shown in FIG. 1, bottlenecks 122 may occur during the transmission from the content server 102 to the ISPs 104, 106 and 108 and during the transmission from the ISPs 104, 106 and 108 to the end users. The bottlenecks 122 reduce viewing quality and access speeds, and increases viewing costs as ISPs pass on bandwidth access or rental costs to the end
- 30 users. Further, when data packets are lost the end user request for

retransmission of that data must be sent back to the content server 102, this retransmission introduces redundant bandwidth utilization effecting all users connected to the server. The addition of bandwidth to overcome this problem is currently very costly to ISPs. Furthermore, because bandwidth
5 constraints are defined by the lowest capacity hop between the content source and the end user, capacity additions to one Internet segment does not necessarily improve overall capacity.

A second problem with the existing transmission scheme is that the Internet does not provide for the most time or cost effective routing of
10 content to end users. In other words, the data travels through more devices (and thus more hops) than would otherwise be optimal. This not only leads to a reduction in viewing quality and access speed, but also reduces the ability of content providers to track and manage the distribution of proprietary content.

15 The most common method that ISPs employ to manage the dual problems of bandwidth constraint and inefficient routing is to locate dedicated streaming media servers (SMS) within the ISP LAN, to locally store and redistribute content to ISP customers. However, there are a number of problems with this approach. Typically, an ISP can manage the
20 aggregated bandwidth requirement of a plurality of clients streaming a plurality of data packets within the LAN if the data is from a server located within the ISP LAN. Costs to maintain and manage such servers are expensive. Additionally, content providers are often reluctant to provide content to autonomous operators when copyright protection and
25 royalty/licensing fees are at issue. A further disadvantage of having an autonomous local server is that the storage capacity of the server often limits the choice of content available to the ISP clients. Clients often must access stream media through the WAN.

Therefore, there is a need for a more efficient system and method for the distribution content. Furthermore, there is a need for a universal Streaming Media distribution system.

SUMMARY

The present system and method overcomes or substantially alleviates prior problems associated with data transmissions over the Internet. In general, the present system and method provides an intelligent distribution network (IDN) which optimizes delivery of content to large and diversely located client locations by minimizing the impact of network irregularities, minimizing bandwidth usage inherent in data delivery from a single content source to multiple simultaneous viewers, minimizes packet loss resulting in a decrease latency of data stream delivery, maximizes sustained data rates to clients, and provides a back channel of end-user viewing profiles to content providers via the log collection from nodes

The system includes two main components, at least one IDN node and at least one IDN center. When a client requests data from anywhere on the Internet, the client is directed to a preselected IDN center which in turn refers the client to its best performance IDN node. The IDN node then delivers the data to the client over the best performance network link, which may include a plurality of asynchronous transmission devices. The best performance nodes and links are determined by a mapping engine through the use of trace route results between the preselected IDN center, the IDN nodes, the various transmission devices, and the client.

A preferred embodiment of the system and method only requires a SMS to serve one stream to an IDN node, which in turn temporarily buffers the stream in its cache and may relay the content through further nodes and transmission devices to the client. The IDN system may also invoke load sharing between IDN nodes when demand is high therefore maximizing streaming resources of the aggregated IDN nodes within an ISP.

In a further embodiment, nodes may be grouped into zones with each zone having at least one zone master. These zone masters alleviate some of the system management responsibilities of the IDN center, such as the

mapping control functions and log retrieval tasks, and thus increase the efficiency of the IDN system.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of data transmission paths;

FIG. 2 is a diagram of exemplary transmission paths, according to the present system and method;

5 FIG. 3 is a block diagram of an IDN center of FIG. 2;

FIG. 4 is a diagram of exemplary zones within an area, according to the present system and method;

FIG. 5 is a block diagram of exemplary components of a zone master;

10 FIG. 6 is a flow diagram of an exemplary IDN node and router topology including an IDN Center and a client;

FIG. 7 is a diagram of an exemplary communication process, according to the present system and method; and

FIG. 8 is a diagram illustrating error recovery according to the present system and method.

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present system and method comprises an intelligent distribution network (IDN) for the efficient distribution of content. The IDN system further includes at least one IDN management center and at least one node.

5 The IDN system insures the efficient delivery of media content by limiting the number of content streams to a minimum and using the best performing nodes and links to stream the content. This system results in conservation of bandwidth and a reduction in latency, data packet loss, and unacceptable packet delay.

10 FIG. 1 illustrates a preferred content stream 120 over an IDN system as compared to a conventional method. According to the IDN system, only one content stream 120 is sent from the content server 102 across the WAN to a downstream node located in ISP2 106. The downstream node in ISP2 106 may be both a delivery node (the last node to receive the content before
15 streaming to end users) and a transient node (node located between the content provider and the delivery node which "passes" the content along) to nodes in ISP1 104 and ISP3 108. Each ISP may locally redistribute the stream data for service within its own LAN. Each node is also capable of buffering and duplicating copies of the same stream thus allowing second and
20 subsequent users to "piggyback" off the original content stream with the duplicated copies. Furthermore, each ISP contains multiple nodes therefore forming multiple points that allow second and subsequent users to "piggyback" off the original content stream thus further reducing the potential for bottlenecks.

25 Fig. 2 is an illustration of exemplary transmission path architecture between a content provider 202 and a client 214. Client 214 typically selects content from a provider by utilizing a URL on a website. Accordingly, content provider 202, whose content is sourced from streaming media servers (SMS) 204, 206, 208 and 210, forward the content through a Wide
30 Area Network (WAN) 212. In the preferred embodiment this content is

delivered over the WAN 212 or by direct connection to an Intelligent Distribution Network (IDN) center 216, which subsequently forwards the content through various transmission devices and nodes to client 214. Alternatively, the content may be sent directly through various nodes in the IDN system (comprising various transmission devices) to client 214. These nodes, which preferably consist of a computing device running SMS and IDN system software, are placed at divergent data locations on the Internet. Such locations include but are not limited to "bottleneck" routing points.

According to the present system and method, IDN center 216 manages the system such that the most efficient route between content provider 202 and client 214 will be utilized. As shown in FIG. 2, numerous routes are available. The preferred embodiment directs the content to client 214 through the IDN center 216 via path 242 through various routers and nodes. Content may also be transmitted to client 214 through node1 218 and routers G 220 D 222, B 224, A 226, E 228 and H 230. Alternatively, another route may send content via node2 232 and routers F234, C236, E228 and H230.

FIG. 3 is a block diagram of exemplary components of IDN center 216. The IDN center 216 includes an IDN redirection control 302, an IDN system management engine 304 and a web interface engine 306 along with a network interface 308 for communication with the Internet.

IDN redirection control 302 handles requests for content from clients originating from anywhere on the Internet. The IDN redirection control 302 further comprises a mapping engine 310 for mapping points in Internet space and a content management controller 312 for registration of content. Mapping engine 310 performs client location identification, node-client relationship analysis and node-node relay delegations. The results of all these traces are then stored in network trace cache 314 for future use. Basic content provider details would typically be registered with the content management controller 312. For example, this data may include channel

number location, URL details and billing summary data. Registration may be executed through various methods including a standard web interface or programmatically by authorized third parties, which is then stored in a stream database 316.

5 IDN system management engine 304 includes a node controller 318 and a log management controller 320. Node controller 318 receives periodic and event based status information from various nodes such as SMS logs and other network management device logs about network performance and 'billing per bit' usage, and provides updated network information either
10 direct or via propagation to all nodes as required, thus giving enough information to each node about its surrounding environment to overcome most transient problems. Other subsystems of IDN center 216 may also use the information obtained by node controller 318. For example, IDN redirection controller 302 may use this information to override stored node-
15 client maps. A node database 322 stores all the information pertaining to each node. This information may include a node Globally Unique Identifier, IP address (or group of IP addresses), a node's client capacity, client distribution policies including content stream capacity, and scope of client IP classes included/excluded from a particular node.

20 Log management controller 320 compiles and processes log statistics received from the nodes. The compilation of these logs may produce content provider reports, gauge client experiences, and provide feedback on the node-client matching to correct for inconsistencies including routing errors, corrections for time of day, corrections for heavily utilized links, or
25 any such combinations thereof. These logs and compilations are stored in a log-statistics database 324. From the log statistics database viewer profiles and billing information may be extracted by matching client globally unique identifiers with logging information. These viewer profiles and billing information may be used for collating information on what a single viewer
30 watches, the regularity at which they view content and their purchasing

patterns, or what a content providers utilization on the IDN in terms of viewer audience is, and therefore charged.

The interface engine 306 allows network and content provider managers access to the IDN databases, where appropriate, through website database interface 328. Although preferably a web site interface is used, an
5 equivalent interface as is well known in the art may be used to access databases. Because this information may be confidential or proprietary, access to the IDN databases is preferable approved by website access controller 326, which provides security measures. These security measures
10 may include requiring login and password verification or other forms of user identification and control. The managers may then download/upload data and access specific configuration information and statistical analysis with respect to content streams delivered by the system. This information includes a content distribution policy , a content charging policy, a viewer
15 content profile or any other specific policy.

A preferred example of policies as applicable to the IDN System may include but not be limited to; what a customer is charged to watch content, including 'pay per bit' or 'pay per content' as known in the art, the number of clients a node can serve, the number of clients a node can serve for a
20 particular content, the maximum number of clients who can watch the content, the blocking of clients who are banned from content as they have not paid for access or are contained on a black ban list, whether particular content is allowed out of a zone area, and time of day in which content is allowed to be viewed.

25 The following is a description of the IDN system location and redirection technology. Referring back to FIG. 2, when an initial request for a particular content is made, the IDN center 216 will first look up the client's IP class to determine if previous existing information exists in network trace cache 314 (FIG. 3) concerning which node, of the nodes currently relaying or
30 enabled to relay the requested content, is best situated to serve client 214. If

the information does not exist or is outdated, the IDN center 216 will initiate a trace route to client 214 with mapping engine 310 (FIG. 3). The following table shows an exemplary trace route between IDN center 216 and client 214. It should be noted that latency is calculated as the response time between

5 IDN centers 216 and each router or client 214.

| Hop | Latency | Location | IP Address |
|-----|---------|------------|-----------------|
| 1 | 10ms | IDN Center | [192.168.1.200] |
| 2 | 118ms | Router A | [203.168.37.29] |
| 3 | 207ms | Router E | [203.156.34.25] |
| 4 | 217ms | Router H | [203.45.36.127] |
| 5 | 189ms | Client | [210.45.67.78] |

Table A: IDN-Client Trace Table

The result of the IDN-client trace route is then compared to known trace routes contained in a lookup table in network trace cache 314 (FIG. 3) for nodes with the content currently available. Hops of a node trace route result are then matched against the trace route results from IDN center 216 to client 214. The following table shows an exemplary trace route result for the path between IDN Center 216 and node1 218.

| Hop | Latency | Location | IP Address |
|-----|---------|------------|------------------|
| 1 | 10ms | IDN Center | [192.168.1.200] |
| 2 | 118ms | Router A | [203.168.37.29] |
| 3 | 207ms | Router B | [203.156.134.25] |
| 4 | 217ms | Router D | [200.45.36.127] |
| 5 | 189ms | Router G | [210.45.67.178] |
| 6 | 169ms | Node1 | [186.47.167.178] |

Table B: IDN-Node1 Trace Table

And the table for an exemplary trace route result from IDN Center 216 to node2 232 is as follows.

| Hop | Latency | Location | IP Address |
|-----|---------|------------|------------------|
| 1 | 10ms | IDN Center | [192.168.1.200] |
| 2 | 118ms | Router A | [203.168.37.29] |
| 3 | 207ms | Router E | [203.156.34.25] |
| 4 | 207ms | Router C | [193.76.34.25] |
| 5 | 217ms | Router F | [206.45.36.12] |
| 6 | 189ms | Node2 | [134.145.67.178] |

Table C: IDN-Node2 Trace Table

The comparison process will provide a hierarchical estimate of a plurality of most likely 'electronically best performing' network links from known nodes to client 214. While FIG. 2 only illustrates two nodes, in practice, the number of nodes may be quite high, thus the need to determine the 'electronically best performing' links is crucial. IDN center 216 then passes information regarding the best performing links to a detailed interrogation routine in node controller 318 (FIG. 3) that may for further accuracy command the likely best performing nodes to trace the route between themselves and client 214. If the trace is not needed, then the IDN center uses the 'best performing' link as determined by the IDN-node mappings. An exemplary result of a trace between node1 218 and client 214 is shown below.

| Hop | Latency | Location | IP Address |
|-----|---------|----------|------------------|
| 1 | 10ms | Node1 | [186.47.167.178] |
| 2 | 56ms | Router G | [210.45.67.178] |
| 3 | 207ms | Router D | [200.45.36.127] |
| 4 | 217ms | Router B | [203.156.134.25] |
| 5 | 189ms | Router A | [203.168.37.29] |
| 6 | 207ms | Router E | [203.156.34.25] |
| 7 | 217ms | Router H | [203.45.36.127] |
| 8 | 315ms | Client | [210.45.67.78] |

Table D: Node1-Client Trace Route

Similarly, an exemplary trace route result from node2 232 to client 214 is shown below.

| Hop | Latency | Location | IP Address |
|-----|---------|----------|------------------|
| 1 | 10ms | Node2 | [134.145.67.178] |
| 2 | 57ms | Router F | [206.45.36.12] |
| 3 | 207ms | Router C | [193.76.34.25] |
| 4 | 217ms | Router E | [203.156.34.25] |
| 5 | 217ms | Router H | [203.45.36.127] |
| 6 | 189ms | Client | [210.45.67.78] |

Table E: Node2-Client Trace Route

Latency in the above two tables is calculated as the round trip response time from the node to a particular router or client. It is possible that a downstream device may report a lower latency than an upstream device when a downstream device uses a peer link to send a response on a different path back to nodes 218 or 232, the downstream device is heavily loaded with computational tasks, or it has an intrinsically slow response to a trace route request. Because the mapping process works from nodes as well as IDN center 216, peer links and asymmetries of the Internet are discovered and utilized by various algorithms in mapping engine 310 (FIG. 3).

Therefore, it is not unusual to find later trace route hops with shorter times than intermediate hops as they use better paths through better routing tables, or are just faster to respond or less busy. From the results of these two trace routes, node2 232 is tentatively best suited to relay content to client 214 with a network response time of 189ms. Thus, node2 232 is allocated to client 214 as the streaming source and will serve the content stream.

FIG. 2 also shows a peer link 238 connecting router G 220 and router H 230. This peer link 238 may be provided for exclusive data sharing between router G 220 and router H 230. An exemplary trace route result from node1 218 to client 214 through the peer link 238 is shown below.

| Hop | Latency | Location | IP Address |
|-----|---------|----------|------------------|
| 1 | 10ms | Node1 | [186.47.167.178] |
| 2 | 56ms | Router G | [210.45.67.178] |
| 3 | 75ms | Router H | [203.45.36.127] |
| 4 | 77ms | Client | [210.45.67.78] |

Table F: Node 1/Client Trace Route with Peer Link

In this situation, node1 218 would be best able to serve the content stream to client 214 through peer link 238 since the network latency is only 77ms.

- 5 Preferably, client 214 connects directly to node2 232 via a client connection 240. In this instance, an exemplary trace route result yields the following table.

| | | | |
|---|------|--------|------------------|
| 1 | 10ms | Node2 | [134.145.67.178] |
| 2 | 22ms | Client | [210.45.67.78] |

Table G: Node2/Client Trace Route with Client Connection

- 10 Because the network path between node2 232 and client 214 involves only one direct electronic path, latency is low, 22ms. Additionally, because the node is within one network hop to client 214, packet loss and unacceptable delay are significantly reduced, thus resulting in the most efficient network electronic path.

- 15 These mapping calculations between the various nodes and client 214 may be performed simultaneously and typically take less than 500ms. Thus, the cumulative time between the initial trace route from IDN center 216 to client 214 and the consecutive class mapping trace routes from the selected nodes to client 214 can be completed, typically, in a few seconds.

- 20 Additionally, if current mapping information already exists in network trace cache 314 (FIG. 3), then the entire process may be completed even faster.

In a further embodiment, the information gathered through this process may be sent to a neural net system or similar as known in the art for future learning or modification of mappings to more effectively run the IDN system. Furthermore, IDN managers may manually assign node-client

mappings for reasons intrinsic to their own operation such as time of day or other variances.

Once a client is assigned a 'best' or 'nearest' node, the IDN network trace cache 314 is updated with that client's class-node mapping. This result
5 may then be used for any other clients originating from the same class IP address range without going through the class mapping procedure again. Therefore, when a popular site is receiving a plurality of 'hits' from clients within the same class IP address range, a large number of these clients can be directed to their electronically nearest or best node from stored client
10 class-node mapping results contained in network trace cache 314 obtained from an earlier client request (initial request) for the content.

Furthermore, when client 214 is already receiving a stream from a node, any further clients requesting the same content may "piggyback" off the node. This would require the subsequent clients to connect, either
15 directly or indirectly through other nodes or transmission devices, to any node that is currently serving the content to client 214. Once connected, the subsequent clients can obtain data from the same initial content stream. Thus, only one distribution of the content is required to serve multiple clients.

20 Nodes may be grouped into zones based on geographical or market demographic locations. Alternatively, zones may be based on other categories. Zones contribute to the efficiency of the IDN system by segregating content into two sets: global and thus circumnavigating the world (e.g. CNN) and regional (e.g. San Francisco Little League). Because
25 regional content has a much smaller audience, the content is 'contained' within the local regional zone or zones. Thus, the management overhead of the IDN center and the global system is not consumed.

FIG. 4 shows an exemplary IDN network topography incorporating a zoning system based on autonomous system (AS) maps. Autonomous
30 systems are defined through the Boarder Gateway Protocol (BGP) as known

in the art. Typically, an autonomous system is a set of class of IP address that may belong, for example, to one particular ISP. The network includes two areas, Area1 402 and Area2 404 located in a geographically different location from Area1 402. Area1 402 contains its own IDN center 406 that controls
5 zone masters 408, 410, 412 and 414. As shown in FIG. 4, a second tier zone master (zone master 414) may be included within a first tier zone (such as zone master 406). These zone masters in turn control a plurality of downstream nodes. For example, zone master 406 controls nodeG 416 and nodeJ 418. Similarly, Area 2 404 contains an IDN center 420 that controls
10 first tier zone masters 422, 424 and 426 and second tier zone master 428.

In the preferred embodiment, IDN centers 406 and 420 share information at a top level including location compiled lookup tables and other gathered network intelligence. IDN centers 406 and 420 in turn communicate with their first tier zone masters 408, 410, 412, 422, 424 and 426
15 and directly connected nodes such as node H 430. The communications are subsequently streamed "down the line" to the downstream nodes. It should be noted that the last tiers of the downstream nodes may be connected to further nodes, transmission devices or to clients (not shown). Additionally, alternative node and zone master configurations may be utilized within each
20 area.

In regards to Area1 402, zone masters 408, 410, 412, and 414 are central node locations that may be assigned additional functionality in order to relieve IDN center 406 of individual attention to some downstream nodes. Thus, zone masters 408, 410, 412 and 414 form a buffer zone between the
25 downstream nodes and IDN center 406. The functions of these zone masters will be discussed in more detail in connection with FIG. 5.

Zones master 412 and 426 represent a plurality of additional zone masters. Because content may enter the IDN system from any node within the system, a user from one zone area may seek content that is effectively
30 sub managed in another zone. In this situation, zone master 412 must

communicate with zone master 410 that control the requested content. Accordingly, cached quasi-static information and mappings that are high in demand may be forwarded into zones, which in turn handle much of the network traffic for the content.

5 Assignment of nodes to zone masters will be based on a node's location and the number of nodes in the downstream chain. If the number of nodes downstream is high, a zone master will be likely assigned to assist the IDN center 406.

FIG. 5 shows exemplary components of a zone master 500 that
10 include a node manager 502, a log processing engine 504 and a matching engine 506. Zone master 500 communicates through the Internet via network interface 508. Node manager 502 is responsible for managing downstream nodes within the zone. Management includes receiving
15 periodic and event based status information from the nodes, reporting status and network configuration changes within the zone to IDN center, and providing updated network information to the nodes. Log processing engine 504 will pre-process node logs prior to forwarding the information to the IDN center. By pre-processing the information, resources and available
20 bandwidth is utilized more efficiently. Finally, matching engine 506 performs node-client matching of downstream node locations. This matching engine 506 processes a similar functionality to the mapping engine 310 (FIG 3) in the IDN center 216 (FIG 2). A client first requests content from an IDN center which in turn forwards the request to zone master 500 where matching engine 506 is assigned the mapping responsibility to allocate a
25 node-client assignment. The decision to forward a client request to a zone master is made by the servicing IDN center after an address class match is found to be associated with a zone master. In this situation the client is simply redirected to the zone master without any further processing at the IDN center.

The following is a description of how Location Compiled Tables (LCT) is used by the IDN system. In the preferred embodiment the IDN system uses mapping engine 310 (FIG. 3) or matching engine 506 (FIG 5) to trace routes to each of the nodes in its management area. The result of one exemplary trace route is shown below.

| IP Address | Hop 1 | Hop 2 | Hop 3 | Hop 4 | Hop 5 | Hop 6 | Hop 7 | Hop 8 | Hop 9 | | Hop 31 | Hop 32 |
|-----------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|------|-----------|-----------|
| aaa.bbb.ccc.ddd | A | B | C | D | G | N | AG | KW | ZG | | KHLQ | TSUH |

Table H: Trace Route Results to Node Located within a Zone

The IP address of the node is "aaa.bbb.ccc.ddd", and the trace results show 32 hops each with an intermediate IP address (represented by capital letters) on the path to reach the node. Thus with the first router (Hop 1), IDN mapping engine 310 (FIG. 3) or matching engine 506 (FIG 5) determines its location to be a unique IP address represented by "A". At this point the IDN system is not interested in latency. Instead, the IDN system is only mapping paths defined by the intermediate router IP addressed to each node.

The trace results to all nodes in the zone are then placed in a LCT by ascending hop unique results. An exemplary LCT has the following format wherein the IP address in each cell of the table is represented, for simplicity of this example, by unique letters.

| Hop 1 | Hop 2 | Hop 3 | Hop 4 | Hop 5 | Hop 6 | Hop 7 | Hop 8 | Hop 9 | | Hop 31 | Hop 32 |
|----------|----------|----------|----------|----------|----------|----------|----------|----------|------|--------|--------|
| A | B | C | D | F | L | AC | KS | ZC | | KHL | TSUD |
| | | | E | G | M | AD | KT | ZD | | KHLN | TSUE |
| | | | | H | N | AE | KU | ZE | | KHLO | TSUF |
| | | | | I | O | AF | KV | ZF | | KHLP | TSUG |
| | | | | J | P | AG | K | ZG | | KHLQ | TSUH |
| | | | | K | Q | AH | KX | ZH | | KHLR | TSUI |
| | | | | | R | AI | KY | ZI | | KHLS | TSUJ |
| | | | | | S | AJ | KZ | ZJ | | KHLT | TSUK |
| | | | | | T | AK | LA | ZK | | KHLU | TSUL |
| | | | | | U | AL | LB | ZL | | KHLV | TSU |
| | | | | | V | AM | LC | ZM | | KHL | TSUN |
| | | | | | W | AN | LD | ZN | | KHLX | TSUO |
| | | | | | X | AO | LE | ZO | | KHLY | TSUP |
| | | | | | Y | AP | LF | ZP | | KHLZ | TSUQ |
| | | | | | Z | AQ | LG | ZQ | | KHM | TSUR |
| | | | | | AA | AR | LH | ZR | | KHM | TSUS |
| | | | | | AB | AS | LI | ZS | | KHM | TSUT |
| | | | | | | | | | | | |

Table I: Location Compiled Table (LCT)

Typically, mapping engine 310 or matching engine 506 is located on a server or workstation within a hosting facility. Therefore, data from mapping engine 310 or matching engine 506 will likely travel through several routers before reaching the Internet backbone. Thus in the exemplary LCT above, all the trace results have the same first three hops indicating that the data always has to go through the same three routers (or other transmission devices) to reach the Internet backbone. It is at hop 4 where there is a divergence - more than one router available. By hop 6, 17 unique routers are responding to mapping engine 310 or matching engine 506. As we increase hops, the LCT maps every single router in the participating ISPs. For efficiency, the compilation of the LCT may occur offline and be updated at intervals of time, thus conserving bandwidth at the IDN Center and zone

master while keeping the LCT current. Within a management area, there may be a thousand ISPs each with 10 points of presence (ideal place for an end user node) each hosting a node of the IDN system. Thus, the trace performed by the mapping engine 310 or the matching engine 506 may give
5 10,000 results for one management area.

The LCT is used to compile a Best Performing Node Index (BPNI). For each cell entry in the BPNI there consists of a small data set of the prioritized 'nearest', 'cheapest' or other weighting criteria, set of nodes that are relevant to that particular electrographic location. In the preferred
10 embodiment these set of nodes are called the 'best performing' nodes. Every unique router address contained in the LCT has an entry in the BPNI.

The BPNI is created by first compiling a complete table of node network IP addresses in the forward direction for each cell. A node network IP address is defined as the IP address of the router that lies in the same
15 network as the node. The node network addresses are then sorted based on a node sort algorithm (NSA). The IDN center 216 or zone master 500 may weight various factors when creating this raw table such as network bandwidth, historical performance, transmission time, transmission reliability and other factors constituting 'quality of service' attributes when
20 processing the NSA.

FIG 6 indicates an exemplary routing topology to five nodes AD 609, AG 610, AL 613, LB 614 and LD 615, and nine routers A 602, B 603, C 604, D 605, G 607, N 608, P 611, and AK 612 in relation to an IDN center 601 and a client 620 (as per the exemplary LCT - Table I). In the preferred embodiment
25 best performing node order is determined by traversing the topology tree of the LCT in a forward direction from a first unique router address. Nodes are given a weight based on hop count from this first unique router address. When all forward looking nodes have been registered the process is repeated for the unique router address at the location one hop closer to the
30 IDN center 601 relative to the first unique router address. Further nodes

discovered not previously registered have their weightings increased by a delta amount to reflect that if these nodes are used then data will first have to be delivered from this node back to the IDN center 601 to the divergent router location and then from the IDN center 601 forward to the client 620.

- 5 Discovered nodes are then inserted into an ordered list (order based on weight) and truncated at a predetermined number. The predetermined number of the top priority nodes are then saved in the BPNI. This predetermined number is a best performing node count (BPNC). In a preferred embodiment, the BPNC is set to five, although other values may
10 be used. If the NSA provides a list of nodes that is greater than the BPNC, then only the top results (truncated at the NSA variable length) are stored in the BPNI.

Shown below is an exemplary table of z-dimension data (BPNI) for three sample cells.

| Preferred | Hop5/G | Hop6/N | Hop7/AG |
|-----------|--------|--------|---------|
| 1 | AD | AD | AG |
| 2 | AG | AG | AD |
| 3 | AL | AL | AL |
| 4 | LB | LB | LB |
| 5 | LD | LD | LD |

- 15 Table J: Three Sample Cells Taken from the Best Performing Node Index

For example, hop 7 from an exemplary IND-Client trace route result (Table K) gives a location represented as AG 610. The BPNI of AG is shown above having five prioritized nodes. The IP addresses of these prioritized nodes are represented by AG 610, AD 609, AL 613, LB 614 and LD 615.

- 20 BPNI is also shown for sample hop 6 location N and hop 5 location G 607.

The following describes how a client is redirected to the 'closest' node. Assuming that a client is connecting for the first time (no cache data is available) the IDN trace engine will actively calculate the route to the client KW 611 and return the route as represented in exemplary IDN Center -

- 25 Client trace route result, Table K. An IDN Location Algorithm (IDNLA), a

- component of the mapping engine 310 (FIG 3) stored in the IDN center or where delegated in the matching engine 506 (FIG 5) stored in a zone master, takes the IDN center – client trace route result and counts the number of hops it contains. For example, if the client is eight hops from the IDN center at a location KW 611 then the IDNLA will look in the BPNI for a match on the (number of hops to the client – 1) trace route result (hop7) being address AG 610.

| Client | Hop1 | Hop2 | Hop3 | Hop4 | Hop5 | Hop6 | Hop7 | Hop8 |
|--------|------|------|------|------|------|------|------|------|
| 1 | A | B | C | D | G | N | AG | KW |

Table K: Exemplary IDN Center - Client Trace Route Result

The following is an exemplary BPNI Unique Router Address Table.

| Index | Node Network Address |
|-------|----------------------|
| 1 | L |
| 2 | R |
| 3 | AA |
| 4 | AB |
| 5 | AG |
| 6 | AL |
| 7 | LB |
| 8 | LD |
| 9 | LZ |
| 10 | MI |
| 11 | MN |
| 12 | PO |
| 13 | PQ |
| 14 | PS |
| 16 | PZ |
| 17 | QA |
| 18 | QD |
| | |

Table L: Exemplary Best Performing Node Index Unique Router Address Table

The matching of trace route hop results against the exemplary BPNI Unique Router Address Table (Table L) is preferably performed using an

iterative method. A first guess of one half of the total index length of rows in the exemplary BPNI Unique Router Address Table is used. Thus, if the exemplary BPNI Unique Router Address Table has 1038 entries, then the first guess is 519, which gives an exemplary IP address ZPI. Because this index guess IP address is greater than the AG IP address we are trying to match, the previous index guess is halved and either added to the previous guess (if it was too small) or subtracted from the previous guess (if it was too large). In this case, the true result (index 5 - Table K) is less than the guessed index of 519. Thus, the guessing algorithm will follow the following

computation method:

Column Row Index = 1038

| Guess No. | Computation | Index No. |
|-----------|--|-----------|
| 1 | $1/2 \times 1038$ | 519 |
| 2 | 519 - integer part of $(1/2 \times 519)$ | 259 |
| 3 | 259 - integer part of $(1/2 \times 259)$ | 129 |
| 4 | 129 - integer part of $(1/2 \times 129)$ | 65 |
| 5 | 65 - integer part of $(1/2 \times 65)$ | 33 |
| 6 | 33 - integer part of $(1/2 \times 33)$ | 17 |
| 7 | 17 - integer part of $(1/2 \times 17)$ | 9 |
| 8 | 9 - integer part of $(1/2 \times 9)$ | 5 |

Table M: Guessing Algorithm for Matching BPNI Unique

Router Address Table Cell

Thus, in the exemplary BPNI, a 1038 entry index can resolve in eight computational steps. If no match is found, then the system may either try to find a match using the previous hop (in the example above, hop 6) of the IDN Center - Client trace Route Result and the BPNI Unique Router Address Table thus moving back a hop. If a match is again not found the process described iterates back one hope at a time on the IDN Center - Client Trace Route Result until a match is found.

Once this match is found, the BPNI of the resolved cell provides the five best performing nodes in order of priority. The IDN system can then send the client to the highest priority node, load share to a lower priority

node, or instruct all or some of these five nodes to perform a cross trace route from the node to the user and return the results to the IDN center 216 or zone master 500 for further analysis before assigning a best performing node to the client. This entire process only takes a few seconds in the first
5 instance, and even less time if client trace results are stored and the BPNI Unique Router Address Table is current (thus eliminating the need to run a trace route to the client and preferred nodes in the zone).

Class mapping may be used to associate client IP addresses by the mapping engine 310 or matching engine 516 such that the resultant best
10 performing node found for the first client from within a class map is used for all other client from within the same class map until the BPNI expires, or another decision is made to renew the result of the best performing node for that client class map.

Once the best performing node is determined for a client, the
15 requested media may be served to the client. FIG. 7 illustrates a preferred communication process between nodes in the IDN system for transmission of live streaming media content. Initially, a client 702 sends a request 704 to IDN center 706, which responds with 708 to client 702 by redirecting it to a media server 710 and node control component 711 in the 'nearest' node, IDN
20 node D 712, as determined by the trace route results previously discussed. The node control component 711 instructs the SMS 710 via the SMS API functions 720. IDN center 706 then controls the communications between nodeD 712 , nodeC 714, nodeB 716 and media source 718 to set up the most efficient transient delivery path for the stream of content.

25 Any further clients who request the same content from IDN center 706 will be redirected to their nearest transient point (i.e. node B716, node C714 or node D712), as determined by the IDN center 706, for immediate access to the single content stream. Alternatively, the IDN can create another stream transient path to nodes closer to the further clients using
30 node B716, node C714 or node D712 as part of the new transient path.

Therefore, various nodes within the IDN system may become the virtual content sources for the streamed content, eliminating the need for each client to access the original media source 718. The result is that one stream to client 702 may be simultaneously streamed to a plurality of other clients.

5 This process is known as piggybacking. The piggybacking process is made further efficient by redirecting clients to their best performing delivery node that may already be actively transmitting the media content. This best performing delivery node is typically a node located close to each client, thus minimizing network traffic.

10 In a preferred embodiment, after client 702 is directed to best performing delivery node D 712 and while the content stream is being configured, client 702 may be shown locally cached multimedia content. Upon sourcing the content stream, notification is sent down the "chain" of transient nodes B 716 and C 714 until delivery node D 712 is reached, at
15 which time the content becomes seamlessly available to client 702.

In an alternative embodiment, the IDN system utilizes a delivery method based on "channels" similar to television broadcasts. Thus, instead of configuring each server with a different stream name for each content broadcast, a set of pre-configured channels will exist. Streaming media
20 content is then allotted a time slot on one of these channels. Thus, multiple simultaneous events may be streamed concurrently on separate channels, or channels may be used to transmit delayed copies of the same content allowing channel selection as a form of dynamic fast forward and rewind. Furthermore, a client may be directed to locally cached content while being
25 connected to the requested content stream. This locally cached content may include advertising or information relevant to local users only.

Occasionally, the IDN system may experience an error or failure mode. There are two main node errors, transient errors and source stream error. Transient errors may occur when the delivery node fails or a node or
30 link between the media source and the delivery node fails. With a transient

error, the zone master (or IDN center if there is no zone master), after receiving notice of the problem, will attempt to directly poll the node in question. If a status is returned from the node then the zone master will assume that the error is a client side problem. However, if there is no
5 response, the zone master will poll a downstream node to confirm a node outage, as oppose to a link failure. In either case, the IDN center will be notified via the zone master of the problem and will take appropriate steps, including not directing further clients to the problem node.

In contrast, source stream errors occur either when configuring
10 content for delivery or during the delivery, itself. In either case, all nodes may detect a source failure and activate the appropriate recovery procedures. First, the detecting node(s) will poll its upstream node, which in turn polls the next upstream node until the point of failure is discovered or the zone master (or IDN center) is reached. Nodes may make assumptions
15 in relation to the outage. For example, if other content continues to be delivered, a simple source failure is assumed, and the client may be switched to a locally cached "outage" status video.

FIG. 8 illustrates an exemplary method of recovering from a node failure. As shown in event1 800, client 802 is down streamed media through
20 nodesA, C, D, E, 804, 806, 808, 810 and delivery nodeF 812. In event2 814, node C 806 experiences a failure. Downstream nodes D, E and F 808, 810 and 812 detect an error when the content is no longer streamed. NodeE 810 and nodeF 812 will poll their respective upstream node and await the results. NodeD 808 will detect that nodeC 806 is not responding. Upon receiving a
25 status request from nodeE 810, nodeD 808 will return a "please standby" status.

Because nodeC 806 has completely failed, nodeD 808 must find an alternate upstream source node. NodeD 808 will check an algorithm 816 listing best performing surrounding nodes from data contained in a node
30 configuration file, and attempt to connect based on the algorithm 816

illustrated in event3 818. The algorithm node listing maybe similar to the best performing nodes contained in the BPNI. As shown in algorithm 816, the next nearest node is nodeB 820. Thus, in event4 822, nodeD 808 connects with nodeB 820, and a status message will be delivery to nodeE 810, and
5 subsequently nodeF 812, that the source is once again available. It should be noted that these nodal operations would occur asynchronously resulting in a recovery that is extremely rapid from the point of failure. In fact, it is likely that the client will not even perceive an interruption of service.

It is applicable that a client may request multiple streams from the
10 IDN system. These concurrent streams may be buffered at the client computer device or the delivery node and timing information contained in the stream is used to synchronize the streams such that the streams are viewed and or heard concurrently. This method may also be used to achieve augmentation layers in MPEG coding as known in the art.

15 In a further embodiment the system as described is used to find the best performing server with respect to network performance for a client, for application such as online gaming and other general Internet technologies. Additionally, BPNI can be compiled for categories of on-demand content. Thus the redirection system described herein can be used for general data
20 location, and the content distributed may be on-demand content.

The node control component 711 may in part, or in full, be incorporated into an operation system such as Microsoft Windows NT and run as a system service. Through remote method invocation or socket interface as known in the art remote computers may be controlled from a
25 central location. Through this interface mapping functions may be performed on behalf of the IDN system and return the results for inclusion into Internet network performance maps. In such an embodiment the IDN system described herein can be used in part or in full as a component of an operating system for general distribution through the universal market as a
30 useful function for all code applications.

In a further embodiment the mapping functions running as a system service, as described previous may be used by a computer operating system to allow computers to interact and form network point to point links under the direction of an IDN center. These links may include routing instructions applied to the data as it is sent from the source PC. Such application may include video conferencing or IP telephony whereby a most efficient data path may be found using IDN nodes between a first computing device to a second computing device. In this application, a first computing device requests an IDN center to assist in establishing a video conference or a packet switched telephone call to a second computing device. Another application is for the first computer device to request an IDN center to form a permanent, or temporary network link between the first computer device and the second computer device such that they may more efficiently share data.

In a further embodiment the IDN system can be used to manage packet switch telephony applications and devices such as WAP, G2, G2.5 and G3 mobile phones. By using the nodes unique path management procedures as described in this patent the voice or video data can be directed to client telephones or a personal digital assistant (PDA) device. Issues that are important to these telephony packet switched infrastructure are minimizing dropped packets, efficiently handling re-request of data packets lost or unacceptably delayed in transmission, and minimizing network path distances between the server and client, which through the IDN system can be virtual served at node locations thus improving throughput. It is typical of these telephone devices and infrastructure that a user can be located to within nine meters geographically. The IDN system can be used to associate this user to the IDN electrographic data and therefore form electrographic maps that contain geographic information or geographic maps that contain electrographic data.

In yet a further embodiment the mapping technology described herein may be used to create a new generation of router devices. These router devices act like routers as known in the art, but host all or part of node functionality that is controlled from at least one IDN center.

5 The IDN system embodies excellent Quality of service attributes as, when high quality of service (high priority) clients request streaming media, the system can downgrade lower quality of service (low priority) clients who are already receiving streams at a higher quality of service than they need (or have paid for) by switching them to a less optimal and/or cheaper
10 path to make way for the new high priority client.

 The invention has been described above with reference to specific embodiments. It will be apparent to those skilled in the art that various modifications may be made and other embodiments can be used without departing from the broader scope of the invention. Therefore, these and
15 other variations upon the specific embodiments are intended to be covered by the present invention, which is limited only by the appended claims.

WHAT IS CLAIMED IS:

1. A system for efficient distribution of data to a client through a distributed computer network, comprising:
a management center connected to the network for determining an optimal delivery route to the client and directing the data along the optimal delivery route; and
at least one node connected to the network for relaying the data for delivery to the client.
2. The system of claim 1 wherein the at least one node buffers the data before replicating a plurality of the data for delivery to multiple clients.
3. The system of claim 1 wherein the at least one node buffers the data before replication.
4. The system of claim 1 further comprising at least one content provider, the content provider providing at least one stream of data to the network.
5. The system of claim 1 further comprising at least one zone master for assisting the management center with managing downstream nodes.
6. The system of claim 1 wherein the management center further comprises a mapping engine for mapping trace routes between the management center, at least one node and the client in order to determining the optimal delivery route.

7. The system of claim 1 where in the management center further comprises a content manager for managing registration of content provider details.
8. The system of claim 1 wherein the management center further comprises a node controller for monitoring and informing the at least one node.
9. The system of claim 1 wherein the management center further comprises a log management controller for compiling and processing log statistics received from the at least one node.
10. The system of claim 1 wherein the management center further comprises an interface engine for allowing access to management center databases.
11. The system of claim 1 wherein the data is distributed via channels.
12. The system of claim 11 wherein the data is time-staggered versions of identical content to achieve virtual fast-forward and rewind.
13. The system of claim 11 wherein clients are delivered local content at predetermined or incident-invoked times for a predetermined duration.
14. The system of claim 1 wherein the data is packet switched telephony data.
15. The system of claim 1 wherein the data is video conferencing data.
16. The system of claim 1 wherein the data is live media content.

17. The system of claim 1 wherein the data is general Internet data.
18. The system of claim 1 wherein the data is on-demand content.
19. A system for distributing a single stream of data from a content provider through a distributed computer network to a plurality of clients within a class IP address range, comprising:
- a management center connected to the network for determining an optimal delivery route to a first client within the plurality of clients and directing the stream of data along the optimal delivery route;
 - a first optimal node connected to the network for replication of the stream of data for delivery to the first client; and
 - a second optimal node connected to the network for replication of the stream of data for delivery to a second client.
20. The system of claim 19 wherein the first and second optimal nodes are the same.
21. The system of claim 19 wherein the first and second optimal nodes replicate a plurality of the stream of data for delivery to the plurality of clients.
22. A method for distribution of data to a client through a computer network, comprising the steps of:
- determining an optimal delivery route from a content provider to a client;
 - transmitting a data stream from the content provider through the network;
 - receiving the data at an optimal node to the client; and

relaying the data for delivery to the client.

23. The method of claim 22 further comprising the step of transmitting the data through a path of a plurality of nodes before reaching the optimal node.

24. The method of claim 23 wherein a management center determines the path.

25. The method of claim 22 further comprising the step of substituting content local to the optimal node into the data stream.

26. A method for distribution of a single stream of data to a plurality of clients within a class IP address range, comprising the steps of:

determining an optimal delivery route from a content provider to a first client within the plurality of clients;

receiving the stream of data at a first optimal node to the first client and duplicating the stream of data for delivery to the first client;

determining an optimal delivery route to a second client within the plurality of clients; and

receiving the stream of data at a second optimal node to the second client and duplicating the stream data for delivery to the second client.

27. The method of claim 26 wherein the first and second optimal nodes are the same.

28. A method for determining an optimal delivery route from a content provider to a client within a network, comprising the steps of:

obtaining a trace route from a management center to the client;

determining most efficient network links from nodes within the network to the client; and

selecting the most efficient network link as the optimal delivery route.

29. The method of claim 28 wherein the step of selecting further comprises performing trace route mappings between the node of the most efficient network link and the client to determine the optimal delivery route.

30. The method of claim 28 wherein the step of determining further comprises performing trace route mappings between the management center and the nodes.

31. The method of claim 28 wherein the step of determining further comprises accessing a database in the management center containing trace route data for the nodes.

32. The method of claim 28 wherein the step of determining further comprises accessing a location compiled table for node location data within a zone.

33. The method of claim 28 wherein the step of determining further comprises accessing a best performing node index unique router address table.

34. A system for distributing a single stream of data from a content provider to a plurality of clients through a distributed computer network, comprising:

means for determining an optimal delivery route from the content provider to a first client within the plurality of clients;

means for receiving the stream of data at a first optimal node to the first client and duplicating the stream of data for delivery to the first client;

means for determining an optimal delivery route to a second client;

and

means for receiving the stream of data at a second optimal node to the second client and duplicating the stream of data for delivery to the second client.

35. The system of claim 34 wherein the first and second optimal nodes are the same.

36. A computer readable medium having embodied thereon a program, the program being executable by a machine to perform the method step for determining an optimal delivery route from a content provider to a client within a network, the method steps comprising:

obtaining a trace route from a management center to the client;

determining most efficient network links from the nodes within the network to the client; and

selecting the most efficient network link as the optimal delivery route.

37. The computer readable medium of claim 36 wherein the step of selecting further comprises performing trace route mappings between the nodes of the most efficient network links and the client to determine the optimal delivery route.

38. A method for determining an optimal delivery route from a first computing device to a second computing device within a network, comprising the steps of:

- obtaining a trace route from a management center to the first and second computing devices;

- determining most efficient network links from nodes within the network to the first and second computing devices; and

- performing trace route mappings between nodes of the most efficient network links and the first and second computing devices.

39. A system for efficient distribution of data to a client through a distributed computer network, comprising:

- a management center connected to the network for determining an optimal delivery route to the client and directing the data along the optimal delivery route; and

- at least one router device connected to the network for replication of the data for delivery to the client,

- wherein the optimal delivery route is determined by performing mappings to and from the at least one router device and the management center.

40. A method for streaming media error recovery in an intelligent distribution network due to node failure, comprising the steps of:

- detecting a failed node location;

- determining an alternative source node at a next node downstream of the failed node location; and

- obtaining streaming media from the alternative source node.

41. The method of claim 40 wherein the step of detecting further comprises polling by downstream nodes of their subsequent upstream node until the failed node location is discovered.

42. The method of claim 40 wherein the step of determining further comprises accessing a listing of best surrounding nodes from data contained in node configuration files of the next node downstream of the failed node location.

43. The method of claim 40 further comprising the step of substituting local content in place of the streaming media until completion of error recovery.

44. A system for generating Internet network performance maps, comprising:
at least one management center connected to the Internet for mapping trace routes; and
a plurality of nodes connected to the Internet, the plurality of nodes reporting Internet network performance to the at least one management center.

45. The system of claim 44 further comprising a neural network coupled to the at least one management center for learning the Internet architecture.

46. The system of claim 1 wherein the management center downgrades lower priority clients from a higher quality of service network link to a less optimal network link when a higher priority client requests use of the higher quality of service network link.

47. The system of claim 1 wherein the at least one node is used to buffer and resynchronize multiple streams of content.




FIG. 1

2/8




FIG. 2

3/8




FIG. 3

4/8




FIG. 4

5/8




FIG. 5

6/8




FIG. 6

7/8




FIG. 7




FIG. 8

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU 01/00015

| A. CLASSIFICATION OF SUBJECT MATTER | | | | | | | | | | | | |
|--|--|--|--|---|---|--|---|--|--|---|--|--|
| Int Cl ⁷ : HO4L 12/56 | | | | | | | | | | | | |
| According to International Patent Classification (IPC) or to both national classification and IPC | | | | | | | | | | | | |
| B. FIELDS SEARCHED | | | | | | | | | | | | |
| Minimum documentation searched (classification system followed by classification symbols) IPC:GLOBAL | | | | | | | | | | | | |
| Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched INTERNET | | | | | | | | | | | | |
| Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPAT | | | | | | | | | | | | |
| C. DOCUMENTS CONSIDERED TO BE RELEVANT | | | | | | | | | | | | |
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. | | | | | | | | | | |
| X A | EP 0753952A2 (INTERNATIONAL BUSINESS MACHINES CORPORATION) 15 January 1997 Whole document | 1-39, 44-47 40-43 | | | | | | | | | | |
| X A | EP 0578041B1(INTERNATIONAL BUSINESS MACHINES CORPORATION) 17 November 1999 Whole document | 1-39, 44-47 40-43 | | | | | | | | | | |
| X A | US 5854899A (CALLON et al) 29 December 1998 Whole document | 1-39, 44-47 40-43 | | | | | | | | | | |
| <input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex | | | | | | | | | | | | |
| <p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>"A" Document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E" earlier application or patent but published on or after the international filing date</td> <td>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O" document referring to an oral disclosure, use, exhibition or other means</td> <td>"&" document member of the same patent family</td> </tr> <tr> <td>"P" document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table> | | | "A" Document defining the general state of the art which is not considered to be of particular relevance | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention | "E" earlier application or patent but published on or after the international filing date | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone | "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art | "O" document referring to an oral disclosure, use, exhibition or other means | "&" document member of the same patent family | "P" document published prior to the international filing date but later than the priority date claimed | |
| "A" Document defining the general state of the art which is not considered to be of particular relevance | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention | | | | | | | | | | | |
| "E" earlier application or patent but published on or after the international filing date | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone | | | | | | | | | | | |
| "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art | | | | | | | | | | | |
| "O" document referring to an oral disclosure, use, exhibition or other means | "&" document member of the same patent family | | | | | | | | | | | |
| "P" document published prior to the international filing date but later than the priority date claimed | | | | | | | | | | | | |
| Date of the actual completion of the international search 15 May 2001 | | Date of mailing of the international search report 01 JUNE 2001 | | | | | | | | | | |
| Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200 WODEN ACT 2606 AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No.: (02) 6285 3929 | | Authorized officer SUSHIL AGGARWAL Telephone No.: (02) 6283 2192 | | | | | | | | | | |

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU 01/00015

| C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT | | |
|---|---|-----------------------|
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| X A | IEEE Internet Computing, March-April 1999, McCanne, "Scalable Multimedia Communication" pages 33-45 ✓ Whole document | 1-39, 44-47 40-43 |
| X A | Proceedings of the 1997 International Conference on Network Protocols (ICNP'97), Levine et al, "Improving Internet Multicast with Routing Labels" pages 241-250 ✓ Whole document | 1-39, 44-47 40-43 |
| X | ✓ WO 98/29998A2 (MCI COMMUNICATIONS CORPORATION) 9 July 1998 Whole document | 40-43 |
| X | ✓ EP 0939560A1 (ALCATEL) 1 September 1999 Whole document | 40-43 |
| A | ✓ US 5948055A (PULSIPHER et al) 7 September 1999 Whole document | 1-47 |

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/AU 01/00015

Box I Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

Box II Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See Extra Sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU 01/00015

Box II Continued

The international application does not comply with the requirements of unity of invention because it does not relate to one invention or to a group of inventions so linked as to form a single general inventive concept. In coming to this conclusion the International Searching Authority has found that there are different inventions as follows:

1. Claims 1-39, 46 and 47 are directed to a system or method or computer readable medium for efficient distribution of data to a client through a distributed computer network comprising following integers:

- a management centre connected to the network for determining an optimal delivery route to the client,
- directing the data along the optimal delivery route,
- at least one node connected to the network for relaying the data for delivery to the client.

It is considered that these integers comprise a first "special technical feature".

2. Claims 40-43 are directed to a method for streaming media error recovery in an intelligent distribution network due to node failure comprising following integers:

- detecting a failed node location,
- determining an alternative source node at a next node downstream of the failed node location,
- obtaining streaming media from the alternative source node.

It is considered that these integers comprise a second "special technical feature".

3. Claims 44 and 45 are directed to a system for generating internet network performance maps comprising following integers:

- at least one management centre connected to the internet for mapping trace routes,
- a plurality of nodes connected to the internet,
- the plurality of nodes reporting internet network performance to the at least one management centre.

It is considered that these integers comprise a third "special technical feature".

Since the above mentioned groups of claims do not share any of the technical features identified, a "technical relationship" between the inventions, as defined in PCT rule 13.2 does not exist. Accordingly, the international application does not relate to one invention or to a single inventive concept.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/AU 01/00015

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

| Patent Document Cited in Search Report | | | | Patent Family Member | |
|--|----------|----|----------|----------------------|--------------|
| WO | 98/29998 | AU | 57196/98 | US | 5943314 |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | END OF ANNEX |